PENDING CLAIMS:

1	 (Currently Amended) An apparatus for generating a hybrid speech model associated to a
2	given speech element, said hybrid speech model being suitable for use by a speech recognition
3	device during speech recognition, said apparatus comprising:
4	 an input for receiving an input signal derived from a spoken utterance that contains
5	al least one speech element that potentially matches the given speech element;
6	a model group associated to the given speech element, said model group comprising
7	a plurality of speech models, each speech model of said plurality of speech models
8	being a different representation of the given speech element;
9	a processing unit coupled to the input for processing the input signal and the model
10	group to generate a hybrid speech model associated to the given speech element, said
11	hybrid speech model being a weighted combination of speech models in said plurality
12	of speech models effected on the basis of the input signal derived from the spoker
13	utterance;
14	an output for releasing a signal indicative of said hybrid speech model associated to
15	the given speech element in a format suitable for use by a speech recognition device

- 1 2. (Unchanged/Original) An apparatus as defined in claim 1, wherein the given speech
- 2 element is an element selected from the group consisting of phones, diphones, syllables and words.
- 1 3. (Unchanged/Original) An apparatus as defined in claim 2, wherein said input signal
- derived from a spoken utterance is indicative of a speaker specific speech model associated to the
- 3 at least one speech element.
- 4. (Unchanged/Original) An apparatus as defined in claim 3, wherein said hybrid speech
- 2 model is weighted toward the speaker specific speech model.
- 1 5. (Unchanged/Original) An apparatus as defined in claim 4, wherein said hybrid speech
- 2 model is derived by computing a linear combination of the speech models in said model group.

5

6

7

8

9

10

given speech element.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

6.	(Unch	anged/Origi	nal)	An appa	ratus as de	fined in clair	n 5, wherein	said inpu	t is a first
input a	and whe	rein said in	put signal	is a first i	nput signal	l, said appar	atus further	comprisi	ng:
	a)	a second	input for	receiving	a second	input sign	al conveying	g a data	element
identif	fying the	e given spee	ech eleme	nt;					
	b)	a database	of model	groups con	nprising a p	olurality of n	odel groups,	, each mo	del group
being associated to a respective speech element, each model group comprising a set of speech									
model	ls;								
	said pr	ocessing un	it being fi	arther opera	ative for ex	tracting fron	n said databa	se of mod	el groups
a certa	ain mod	el group ass	sociated to	the data	element re	ceived at sa	id second in	put identi	fying the

2

3

4

5

б

8

9

10

11

12

13

14

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

7. (Currently Amended) A method for generating a hybrid speech model associated to a given speech element, said hybrid speech model being suitable for use by a speech recognition device during speech recognition, said method comprising:

receiving an input signal derived from a spoken utterance that contains at least one speech element that potentially matches the given speech element;

providing a model group associated to the given speech element, said model group comprising a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element;

processing the input signal and the model group to generate a hybrid speech model associated to the given speech element, said hybrid speech model being a <u>weighted</u> combination of speech models in said plurality of speech models <u>effected</u> on the basis of the input signal derived from the spoken utterance;

releasing a signal indicative of said hybrid speech model associated to the given speech element in a format suitable for use by a speech recognition device.

2

3

4

5

б

7

8

10

11

12

13

14

15

16

17

18

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138

(Currently Amended) A computer readable medium comprising a program element suitable 8. for execution by a computing apparatus for generating a hybrid speech model associated to a given speech element, said hybrid speech model being suitable for use by a speech recognition device during speech recognition, said computing apparatus comprising: a memory unit for storing a model group associated to the given speech element, said model group comprising a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element; a processor operatively connected to said memory unit, said program element when executing on said processor being operative for implementing: an input for receiving an input signal derived from a spoken utterance that contains at least one speech element that potentially matches the given speech element; a processing unit coupled to the input for processing the input signal and the model group to generate a hybrid speech model associated to the given speech element, said hybrid speech model being a weighted combination of speech models in said plurality of speech models effected on the basis of the

input signal derived from the spoken utterance;

20

21

1

2

3

6

7

8

9

10

11

12

13

14

15

16

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138

an output for releasing a signal indicative of said hybrid speech model associated to the given speech element in a format suitable for use by a speech recognition device.

(Currently Amended) An apparatus for generating a complex speech model associated to a 9. given speech element, said complex speech model being suitable for use by a speech recognition device during speech recognition, said apparatus comprising:

> an input for receiving an input signal derived from a spoken utterance that contains at least one speech element that potentially matches the given speech element; a model group associated to the given speech element, said model group comprising a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element, said model group comprising two sets of speech models namely a first set having speech models of a first type and a second set having speech models of a second type, each speech model of a first type in said first set being associated to a speech model of the second type in the second set;

a processing unit coupled to the input for:

processing the input signal and the model group to generate a hybrid speech a) model associated to the given speech element, said hybrid speech model being a weighted combination of speech models of the first type in said

plurality of speech models effected on the basis of the input signal derived 17 from the spoken utterance; 18 processing the hybrid speech model to generate a complex speech model b) 19 associated to the given speech element, said complex speech model being a 20 weighted combination of speech models of the second type in said plurality 21 of speech models; 22 an output for releasing a signal indicative of said complex speech model associated 23 to the given speech element in a format suitable for use by a speech recognition 24 25 device.

- 1 10. (Currently Amended) An apparatus as defined in claim 9, wherein any speech model of a second type is indicative of a speech model having a higher complexity than a speech model of a first type to which [it]the respective speech model of a second type is associated.
- 1 11. (Unchanged/Original) An apparatus as defined in claim 10, wherein the given speech element is indicative of a data element selected from the set consisting of phones, diphones, syllables and words.

- 1 12. (Unchanged/Original) An apparatus as defined in claim 11, wherein said input signal
- derived from a spoken utterance is indicative of a speaker specific speech model associated to the
- 3 at least one speech element.
- 1 13. (Unchanged/Original) An apparatus as defined in claim 12, wherein said hybrid
- 2 speech model is weighted toward the speaker specific speech model.
- 1 14. (Unchanged/Original) An apparatus as defined in claim 13, wherein said hybrid
- 2 speech model is derived by computing a linear combination of the speech models of the first type.
- 1 15. (Unchanged/Original) An apparatus as defined in claim 14, wherein said linear
- 2 combination is a first linear combination and is characterized by a first set of parameters indicative
- 3 of weights associated to speech models of the first type, said complex speech model being derived
- 4 by computing a second linear combination of the speech models of the second type, said second
- 5 linear combination being characterized by a second set of parameters indicative of weights associated
- 6 to speech models of the second type.
- 1 16. (Unchanged/Original) An apparatus as defined in claim 15, wherein said first set of
- 2 parameters and said second set of parameters are indicative of substantially same weights.

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255) U.S. SERIAL No. 09/468,138 PATENT

17.	(Unch	anged/Original)	An apparatus as defined in claim 10, wherein said input is a
first i	nput and	wherein said input si	gnal is a first input signal, said apparatus further comprising:
	a)		receiving a second input signal indicative of a data element
		identifying the giver	n speech element;
b) a database of model groups comprising a plurality of m		l groups comprising a plurality of model groups, each model	
		group being associat	ed to a respective speech element, each model group comprising

two sets of speech models namely a first set having speech models of a first type and a second set having speech models of a second type, each speech model of a first type in said first set being associated to a speech model of the second type in the second set;

said processing unit being further operative for extracting from said database of model groups a certain model group associated to the data element received at said second input identifying the given speech element.

7

8

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

18. (Currently Amendment) A computer readable medium comprising:

a first data structure for storing a plurality of model groups, each model group being associated to a respective speech element in a phonetic alphabet, each model group comprising a plurality of speech models, each model group being suitable for use by a processing device; and a second data structure for storing a hybrid speech model associated to a given speech element, said hybrid speech model being a weighted combination of speech models of the first type in said plurality of speech models effected on the basis of an input signal derived from a spoken utterance that contains at least one speech element that potentially matches the given speech element.

1 19. (Unchanged/Original) A computer readable medium as defined in claim 18, wherein
the given speech element is indicative of a data element selected from the set consisting of phones,
diphones, syllables and words.

20. (Currently Amended) A computer readable medium as defined in claim 19, wherein each model group comprises two sets of speech models namely a first set having a plurality of speech models of a first type and a second set having a plurality of speech models of a second type, each speech model of a first type in said first set being associated to a speech model of the second type in the second set, each speech model of the second type being indicative of a speech model having a higher complexity [that]than a speech model of the first type to which the speech model of the second type is associated.



2

3

5

6

7

ATTORNEY DOCKET No. 10693RMUS01U (NORT10-00255) U.S. SERIAL No. 09/468,138 PATENT

l	21.	(Currently Amended) A speech recognition system comprising:
2		an input for receiving an input signal indicative of a spoken utterance that is
3		indicative of at least one speech element;
4		a first processing unit coupled to said input operative for processing the input signal
5		to derive from a speech recognition dictionary at least one speech model associated
6 6	<i>)</i>	to a given speech element that constitutes a potential match to the at least one speech
7	(`	element;
8		a second processing unit coupled to said first processing unit for generating, using
9		a predefined weighting constraint, a modified version of the at least one speech
10		model on the basis of the input signal;
11		a third processing unit coupled to said second processing unit for processing the input
12		signal on the basis of the modified version of the at least one speech model to
13		generate a recognition result indicative of whether the modified version of the at least
14		one speech model constitutes a match to the input signal;
15		an output for releasing a signal indicative of the recognition result.

- 1 22. (Unchanged/Original) A speech recognition system as defined in claim 21, wherein
- 2 said first processing unit is operative for generating a speaker specific speech model derived on the
- 3 basis of the input signal, the speaker specific speech model being indicative of the acoustic
- 4 characteristics of the least one speech element.
- 1 23. (Unchanged/Original) A speech recognition system as defined in claim 22, wherein
- 2 said modified version of the at least one speech model is indicative of a hybrid speech model
- 3 associated to the given speech element.

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

24. (Currently Amended) A speech recognition system as defined in claim 23, wherein said second processing unit comprises:

coupling member for allowing data exchange between the first processing unit and the second processing unit, said coupling member being suitable for receiving the speaker specific speech model derived from the input signal;

a model group associated to the given speech element, said model group comprising a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element;

a functional unit coupled to the coupling member for processing the speaker specific speech model and the model group to generate the hybrid speech model associated to the given speech element, said hybrid speech model being a weighted combination of speech models in said plurality of speech models effected on the basis of the speaker specific speech model;

an output coupling member for allowing data exchange between the second processing unit and the third processing unit, said output coupling member being suitable for releasing a signal indicative of the hybrid speech model associated to the given speech element.

1	25.	(Unchanged/Original)	A speech recognition system as defined in claim 24, wherein
2	said h	aybrid speech model is weig	hted toward the speaker specific speech model.
1	26.	(Unchanged/Original)	A speech recognition system as defined in claim 24, wherein
2	said l	ybrid speech model is deriv	ed by computing a linear combination of the speech models in said
3	group of speech models.		
1	27.	(Unchanged/Original)	A speech recognition system as defined in claim 24, wherein
2	said o	coupling member is a first c	oupling member, said second processing unit further comprising:
3		a) a second coupling	member for allowing data exchange between the first processing
4		unit and the secon	d processing unit, said second coupling member being suitable for
5		receiving a data e	lement identifying the given speech element;
6		b) a database of mo	del groups comprising a plurality of model groups, each model
7		group being assoc	iated to a respective speech element, each model group comprising
8		a set of speech m	odels;
9		said functional unit being	further operative for extracting from said database of model groups
10	a cer	tain model group associate	d to the data element received at said second coupling member

identifying the given speech element.

11

1	28.	(Unchanged/Original)	A speech recognition system as defined in claim 22, who com	
2	said n	nodified version of the at lea	ist one speech model is indicative of a complex speech model	
3	associated to the given speech element.			
1	29.	(Unchanged/Original)	A speech recognition system as defined in claim 28, wherein	
2	said second processing unit comprises:			
3		- coupling member for	or allowing data exchange between the first processing unit and	
4		the second processi	ng unit, said coupling member being suitable for receiving the	
5		speaker specific spe	eech model derived from the input signal;	
6		- a model group asso	ciated to the given speech element, said model group comprising	
7		a plurality of specc	h models, each speech model of said plurality of speech models	
8		being a different r	epresentation of the given speech element, said model group	
9		comprising two set	s of speech models namely a first set having speech models of a	
10		first type and a seco	nd set having speech models of a second type, each speech model	
11		of a first type in sai	d first set being associated to a speech model of the second type	
12		in the second set;		
13		- a functional unit co	oupled to the coupling member for:	
14		a) processing	the speaker specific speech model and the model group to	
15		generate a l	nybrid speech model associated to the given speech element, said	

hybrid speech model being a weighted combination of speech models of the

16

22

23

25

26

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138

first type in said plurality of speech models effected on the basis of the speaker specific speech model;

b) processing the hybrid speech model to generate a complex speech model associated to the given speech element, said complex speech model being a

models;

an output coupling member for allowing data exchange between the second processing unit and the third processing unit, said coupling member being suitable for releasing a signal indicative of the complex speech model associated to the given speech element.

combination of speech models of the second type in said plurality of speech

- 30. (Currently Amended) A speech recognition system as defined in claim 29, wherein any speech model of the second type is indicative of a speech model having a higher complexity than a speech model of the first type to which [it]the speech model of the second type is associated.
- 1 31. (Unchanged/Original) A speech recognition system as defined in claim 30, wherein said hybrid speech model is weighted toward the speaker specific speech model.

A speech recognition system as defined in claim 31, wherein

- said hybrid speech model is derived by computing a linear combination of the speech models of the 2
- 3 first type.

32.

1

- A speech recognition system as defined in claim 32, wherein 33. (Unchanged/Original) l
- said linear combination is a first linear combination and is characterized by a first set of parameters 2
- indicative of weights associated to speech models of the first type, said complex speech model being 3
- derived by computing a second linear combination of the speech models of the second type, said 4
- second linear combination being characterized by a second set of parameters indicative of weights 5
- associated to speech models of the second type. б

(Unchanged/Original)

- A speech recognition system as defined in claim 33, wherein (Unchanged/Original) 1 34.
- said first set of parameters and said second set of parameters is indicative of substantially the same 2
- 3 weights.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

(Currently Amended) An apparatus for generating a hybrid speech model associated to a 35. 1 given speech element, said hybrid speech model being suitable for use by a speech recognition 2 device during speech recognition, said apparatus comprising: 3 means for receiving an input signal derived from a spoken utterance that contains at 4 least one speech element that potentially matches the given speech element; 5 a model group associated to the given speech element, said model group comprising 6 a plurality of speech models, each speech model of said plurality of speech models being a different representation of the given speech element; 8 means for processing the input signal and the model group to generate a hybrid 9 speech model associated to the given speech element, said hybrid speech model being 10 a weighted combination of speech models in said plurality of speech models effected 11 on the basis of the input signal derived from the spoken utterance; 12 means for releasing a signal indicative of said hybrid speech model associated to the 13

given speech element in a format suitable for use by a speech recognition device.

ATTORNEY DOCKET NO. 10693RMUS01U (NORT10-00255) U.S. SERIAL NO. 09/468,138 PATENT

(Currently Amended) A speech recognition system comprising: 36. 1 means receiving an input signal indicative of a spoken utterance that is indicative of 2 at least one speech element; 3 means for processing the input signal to derive from a speech recognition dictionary 4 at least one speech model associated to a given speech element that constitutes a 5 potential match to the at least one speech element; means for generating, using a predefined weighting constraint, a modified version of the at least one speech model on the basis of the input signal; 8 means for processing the input signal on the basis of the modified version of the at 9 least one speech model to generate a recognition result indicative of whether the 10 modified version of the at least one speech model constitutes a match to the input 11 12 signal;

Please add the following new claim(s):

1 37. (Newly Added) An apparatus as defined in claim 15, wherein a relationship between 2 said first set of parameters and said second set of parameters is dependent on a distance between the 3 hybrid model and the input signal.

means for releasing a signal indicative of the recognition result.

An apparatus as defined in claim 37, wherein the processing unit (Newly Added) 38. 1

further comprises:

a fall-back unit conditioning the weighted combination of speech models of the second type

by interpolation to a degree based upon a distance between the hybrid model and the input signal. 4